

PRODUCT : ESTOFLOX P6

Description:

Estoflox P6 is water coloring agent , cationic polymer which is specialized for decoloring, flocculating, COD decreasing and other applications.

Principal uses:

Drinking water application
Waste water treatment
Process water
Water treatment – Coagulants/removal of color

Paper – Coagulants/Fixing agent Textile-Fixing/Flofix

Salient features:

Estoflox P6 has to prepare 2.5-10 % solution that can be dissolved easily in water just prior to application.

Estoflox P6 has a shelf life of 6 months when kept in a dry, cool place. (Away from direct Sun)

Application:

Estoflox P6 has to be diluted with 05 to 10 times water prior to use. Now this solution can added directly to waste water.

Estoflox P6 works best at pH 7.5-8 (of waste water)

It is recommended to use Estoflox P6with anionic flocculants to get better result.

Properties:

Appearance : Clear to hazy liquid

Viscoisty :225-250 cPs

Ionicity :Cationic

pH (30% w/w soln) : 3.5– 5

Solid contents : 50-55 %

Safety, Handling and Storage:

Estoflox P6 is a non toxic and non flammable polymer. As a precautionary measure, safety goggles, rubber gloves are recommended while handling. In case of spillage, contain with sand or soil, wipe dry with cotton waste and then wash.

Caution:

The spill becomes slippery when wet. In case of contact with skin or eyes, wash with water thoroughly. Estoflox P6 has a shelf life of 6 months. It is preferred to store in a cool place, in shed away from direct heat or Sun.

Packing:

Estoflox P6 is available in 50kgs and 200 kgs HDPE barrels

Mfg. of Speciality Chemicals
Surface Coating | Warp Sizing | Lamination | Adhesive

